

ProductName:MK-300M
 Input volt: 12V/24V/48VDC
 Output volt: 110V/220VAC
 ut waveform :Modified sine wave
 Output power: 300W



A	B	C	D	E	F
USA	AUSTRALIA	UNIVERSAL	U.K	FRANCE	GERMANY

Function details

Model	MK-300M-121	MK-300M-241	MK-300M-481	MK-300M-122	MK-300M-242	MK-300M-482
Rated power	300W	300W	300W	300W	300W	300W
Peak power	600W	600W	600W	600W	600W	600W
DC input voltage	12V	24V	48V	12V	24V	48V
AC output voltage	110VAC			220VAC		
No-load current	0.4A	0.2A	0.1A	0.4A	0.2A	0.1A
AC output frequency	60Hz			50Hz		
AC output waveform	Modified Sine Wave					
Efficiency	>85%	>88%	>90%	>85%	>88%	>90%
DC input voltage range	10.5-15V	21-30V	42-60V	10.5-15V	21-30V	42-60V
Low Voltage Alarm	10.5±0.5V	21±1V	42±2V	10.5±0.5V	21±1V	42±2V
Low Voltage Shutdown	10±0.5V	20±1V	40±2V	10±0.5V	20±1V	40±2V
Over Voltage Protection	15.5±0.5V	31±1V	62±2V	15.5±0.5V	31±1V	62±2V
Low Voltage Recovery	12±0.5V	24±1V	48±2V	12±0.5V	24±1V	48±2V
Over Voltage Recovery	14.8V	29.5V	59V	14.8V	29.5V	59V
Protective Function	Low/Over voltage		LED Red light, automatic recovery			
	Over load		LED Red light, automatic recovery			
	Over temperature		LED Red light, automatic recovery			
	Short circuit		LED Red light, automatic recovery			
	Input reverse connection		Fuse burn-out			
Working Temp.	0°C-40°C					
Storage Temp. Humidity	-30°C-70°C					
Dimension	150*95*55mm					
Weight	0.75kg					