

SPH2000 Series

Intelligent charger & inverter -SPH series

Features

- Auto switch 4 FUN: DC to AC , AC bypass, AC charger and UPS
- DIP Switches : Low Battery, AC Input Range , Power Saver, O/P Frequency, Solar/Utility AC Priority
- Efficiency up 3~5% than SPT, Idle consumption down 30~50%
- Output AVR: stabilized AC voltage RMS(optional)
- Start Auto restart while AC is recovering (optional)
- Dry contact: input no AC signal to other device(optional)
- Remote control RJ45/RS232 :PTM-9 and PTM-12(optional)
- Pure sine wave output ,input & output fully isolation
- Input : Utility AC or Generator etc
- Advanced microprocessor control
- Input polarity/UVP/OVP/OSP/OLP/OTP



Specifications

Models	SPH2000-112	SPH2000-124	SPH2000-148	SPH2000-212	SPH2000-224	SPH2000-248
Output Power	2000W					
Surge Power	6000W					
DC Input Voltage	12VDC	24VDC	48VDC	12VDC	24VDC	48VDC
Output Voltage	100/110/120VAC±5%			220/230/240VAC±3%		
Output Frequency	50/60Hz ±0.5%					
Output Waveform	True sine wave (THD<3%)					
Power Factor	0.1~1					
Efficiency	88%	89%	91%	89%	90%	93%
No Load Power	<10W (Power saving mode)					
Transfer Time	<8 ms					
AC Range	184-253VAC (AVR:176-276VAC) /154-253VAC (AVR:150-276VAC) 100-135VAC (AVR:92-144VAC) /90-135VAC (AVR:78-144VAC)					
AVR Output AC	120VAC±10%			230VAC±10%		
Voltage Range	10.0~15.5VDC,*2 for 24VDC, *4 for 48VDC / 10.5~16VDC,*2 for 24VDC, *4 for 48VDC					
Charge Current	70A	30A	15A	65A	30A	20A
Remote Control	RJ45:PTM-9 or PTM-12					
Safety	UL458			LVD (EN60950)		
EMC	FCC Part15 ClassA			CE (EN55022:2006+A1:2007)		
Operating Temp	-20~50°C					
Working Humidity	20~90%RH					
Storage Temp	-30~70°C					
Cooling	Automatically controlled cooling fan					
Weight (kg)	20					
Size (mm)	450*218*180(L*W*H)					

*Note: The Specifications are subject to changes without notice.